
NOTES:

- 1. FOR GRAVITY APPLICATIONS ONLY.
- 2. ALL PROCEPTOR UNITS ARE MANUFACTURED WITH FIBERGLASS REINFORCED PLASTICS. PHYSICAL FIBERGLASS REINFORCED FLASTICS. FITTSICAL CHARACTERISTICS AND THICKNESS:
 POLYESTER RESIN AND E GLASS
 MINIMUM THICKNESS 1/4" WALL AND 3/8" TOP AND BOTTOM BOWLS.
 3. ALL PROCEPTOR UNITS ARE TO BE INSTALLED IN ACCORDANCE WITH THE MANUFACTURERS INSTALLATION INSTRUCTION.

- 4. STANDARD PIPING IS SCH. 40 PVC.
- 5. GMC/OMC 500 3000 UNITS COME STANDARD WITH 4" INLET AND OUTLET (OTHER PIPE SIZE OPTIONS AVAILABLE ON REQUEST).
- 6. EXTENSION COLLAR TO BE ORDERED TO MEET FINISHED GRADE, CUT ON SITE FOR FINAL ADJUSTMENT AND CAULKED WITH SIKAFLEX BY CONTRACTOR FOR WATERTIGHT SEAL.
- 7. COVERS AVAILABLE FOR H20 TRAFFIC LOADING,
- PEDESTRIAN LOADING OR ABOVE GROUND INSTALLATION.
- CONSULT GREEN TURTLE FOR OTHER SIZES.
 30 YEAR WARRANTY AGAINST LEAKS, AND STRUCTURAL FAILURE.
- 10. U.S. PATENT #5,746,912; CDN PATENT #2,195,822







ANCHOR

(1 OF 4)

BRACKET

BAFFLE





FOR UPC/IAPMO INSTALLATIONS APPROVED UNDER PS 80-2008 MEETS ASTM C-581

