


HI-CAP SLOTTED DRAINAGE SYSTEM FOR 18 [457] CORRUGATED PIPE OR EQUIVALENT

Z888-18

SPECIFICATION SHEET

TAG _____

Dimensional Data (inches and [mm]) are Subject to Manufacturing Tolerances and Change Without Notice



ENGINEERING SPECIFICATION: Zurn Z888-18 Slotted Drain channel is 80 [2032] long, 21 [533] deep invert, 12.5 [318] wide with a 1.75 [44] throat width, made from LLDPE linear Low Density Polyethylene. Channels have a mechanical tongue and groove and bolted connection, mechanically lock into the concrete surround every 5 [127] along its length, channels weigh 7.5 lbs. per foot [11.2 kg per meter]. Channel has a smooth 2.5 [64] radiused bottom with a smooth .011 Manning's coefficient, and neutral non-sloping body. Top reveal is non removable and is the finish at the surface, Zip Strip is standard to keep debris out during the construction process. System is anchored into the concrete with Rebar clips or physical anchors every 5 [127] to 10 [254] along the channel body. Integral Rebar Clips are standard. Minimum 2000 psi concrete encasement shall include longitudinal #4 0.5 [13] rebar along chairs on either side of the trench neck. System is capable of Supporting H-20/H-25 Top Load Classification.

PREFIX OPTIONS

Z 80 [2032] linear low density polyethylene modular drain channel with integral top frame.*

SUFFIX OPTIONS

E1	End Cap
E8	8 [203] No Hub End Outlet
E12	12 [305] No Hub End Outlet
E18	18 [457] No Hub End Outlet
E24	24 [610] No Hub End Outlet (Custom Built)
T12/18	Transition from -12 [305] to -18 [457]
T18/12	Transition from -18 [457] to -12 [305]
T18/36	Transition from -18 [457] to -36 [914]

REV. F DATE: 08/23/10 C.N. NO. 111566

*Regularly Furnished Unless Otherwise Specified

DWG. NO. 64088 PRODUCT NO. Z888-18